

teletronik®

LED technology

LED CEILING LIGHTS





LLICE-LWPD260-10M

Product name	Input Voltage	Power (W)	Color temp. (K)	Glass type	Beam angle (°)	Lumen (lm)	Size (L) × Ø
LICE-LWPD260-10M	85-265V AC	10	4000	Milk	120	840	75 × 260mm



LICE-LWPD110-5



LICE-LWPD110-10

Product name	Input Voltage	Power (W)	Color temp. (K)	Glass type	Beam angle (°)	Lumen (lm)	Size (L) × Ø	Drill hole (Ø)
LICE-LWPD110-5C	85-265V AC	6	5000	Transparent	120	440	90 × 125mm	110mm
LICE-LWPD110-5W	85-265V AC	6	3000	Transparent	120	400	90 × 125mm	110mm
LICE-LWPD110-10C	85-265V AC	11	5000	Transparent	120	920	100 × 190mm	170mm
LICE-LWPD110-10W	85-265V AC	11	3000	Transparent	120	800	100 × 190mm	170mm



LICE-BEPDxxx-SMxx

Product name	Input Voltage	Power (W)	Color temp. (K)	Glass type	Beam angle (°)	Lumen (lm)	Size (L) × Ø	Drill hole (Ø)
LICE-BEPD150-SM8C	85-265V AC	8	5000	Milk	50	450	64 × 150mm	130mm
LICE-BEPD150-SM8W	85-265V AC	8	3000	Milk	50	430	64 × 150mm	130mm
LICE-BEPD190-SM14C	85-265V AC	14	5000	Milk	50	825	88 × 190mm	170mm
LICE-BEPD190-SM14W	85-265V AC	14	3000	Milk	50	775	88 × 190mm	170mm
LICE-BEPD230-SM20C	85-265V AC	20	5000	Milk	50	1200	110 × 230mm	200mm
LICE-BEPD230-SM20W	85-265V AC	20	3000	Milk	50	1090	110 × 230mm	200mm
LICE-BEPD230-SM30C	85-265V AC	30	5000	Milk	50	1630	110 × 230mm	200mm
LICE-BEPD230-SM30W	85-265V AC	30	3000	Milk	50	1500	110 × 230mm	200mm