

teletronik®

LED technology

CANDLE, BULB, G24 LAMPS





LR14-BNPCA-3.5W

25W TUNGSTEN	=	3W LED
40W TUNGSTEN	=	5W LED

Product name	Socket	Power (W)	Color temp. (K)	Lens type	Beam angle (°)	Lumen (lm)	Size (L) × Ø
LR14-BNPCA-3.5W	E14	3,5	2700	Milk	145°	250	104 × 37mm
LR14-BNPCA-5W	E14	5	2700	Milk	145°	320	104 × 37mm



LR27-COPBU-270N09W

75W TUNGSTEN	<	9W LED
-----------------	---	-----------

Product name	Socket	Power (W)	Color temp. (K)	Lens type	Beam angle (°)	Lumen (lm)	Size (L) × Ø
LR27-COPBU-270N09W	E27	9	3000	Homogen	300°	680	120 × 60mm
LR27-COPBU-270N09M	E27	9	4500	Homogen	300°	870	120 × 60mm



LR24-ASPD2R-130N07M

13W FLUORESCENT	=	7W LED
18W FLUORESCENT	=	11W LED
26W FLUORESCENT	=	13W LED



Product name	Socket	Power (W)	Color temp. (K)	Beam angle (°)	Lumem (lm)	Size (L) × Ø
LR24-ASPD2R-130N07M	G24D2 (Screwable)	7	5000	130°	570	115 × 35mm
LR24-ASPD2R-130N11M	G24D2 (Screwable)	11	5000	130°	890	115 × 35mm
LR24-ASPD2R-130N13M	G24D2 (Screwable)	13	5000	130°	1050	156 × 35mm